

RDX 2005 Roll Out Chart



The Rug Formula

104T Spur

	Tire Diameter mm																	
final drive	62.50	61.00	61.50	60.00	59.50	59.00	58.50	58.00	57.50	57.00	56.50	56.00	55.50	55.00	54.50	54.00		pinion
5.94	33.039	32.246	32.510	31.717	31.453	31.189	30.924	30.660	30.396	30.131	29.867	29.603	29.338	29.074	28.810	28.545		35.000
6.12	32.067	31.297	31.554	30.784	30.528	30.271	30.015	29.758	29.502	29.245	28.989	28.732	28.475	28.219	27.962	27.706		34.000
6.30	31.151	30.403	30.652	29.905	29.656	29.406	29.157	28.908	28.659	28.410	28.160	27.911	27.662	27.413	27.163	26.914		33.000
6.50	30.192	29.468	29.709	28.985	28.743	28.502	28.260	28.018	27.777	27.535	27.294	27.052	26.811	26.569	26.328	26.086		32.000
6.71	29.247	28.545	28.779	28.077	27.844	27.610	27.376	27.142	26.908	26.674	26.440	26.206	25.972	25.738	25.504	25.270		31.000
6.93	28.319	27.639	27.866	27.186	26.960	26.733	26.506	26.280	26.053	25.827	25.600	25.374	25.147	24.921	24.694	24.468		30.000
7.17	27.371	26.714	26.933	26.276	26.057	25.838	25.619	25.400	25.181	24.962	24.743	24.524	24.305	24.086	23.868	23.649		29.000
7.43	26.413	25.779	25.991	25.357	25.145	24.934	24.723	24.511	24.300	24.089	23.878	23.666	23.455	23.244	23.032	22.821		28.000
7.70	25.487	24.875	25.079	24.468	24.264	24.060	23.856	23.652	23.448	23.244	23.040	22.836	22.632	22.429	22.225	22.021		27.000
8.00	24.531	23.943	24.139	23.550	23.354	23.158	22.961	22.765	22.569	22.373	22.176	21.980	21.784	21.588	21.391	21.195		26.000
8.32	23.588	23.022	23.210	22.644	22.456	22.267	22.078	21.889	21.701	21.512	21.323	21.135	20.946	20.757	20.569	20.380		25.000
8.67	22.636	22.092	22.273	21.730	21.549	21.368	21.187	21.006	20.825	20.644	20.463	20.281	20.100	19.919	19.738	19.557		24.000
9.04	21.709	21.188	21.362	20.841	20.667	20.493	20.320	20.146	19.972	19.799	19.625	19.451	19.278	19.104	18.930	18.757		23.000
9.45	20.767	20.269	20.435	19.937	19.770	19.604	19.438	19.272	19.106	18.940	18.774	18.607	18.441	18.275	18.109	17.943		22.000
9.90	19.823	19.347	19.506	19.030	18.872	18.713	18.555	18.396	18.237	18.079	17.920	17.762	17.603	17.444	17.286	17.127		21.000

best rollout	Motor Winds
	23 mm = 11 T
	22 mm = 10 T
	21 mm = 9 T
	20 mm = 8 T
	35mm = 19 T
	26mm = Stock

Foam Tires	
Fronts	Rears
Plaid or/pur	pur / dbl pur
Plaid or/dbl pink	dbl pink / pink
45 shore	42 - 37 shore

transmission ratio 2.0:1

Rollout by:



badboy@5thscale.com

Ideal tire size is: Stock 60mm Mod/19t 56mm

Copyright Badboy 2005