




Clutch kit for HPI RS-4 Nitro Mini and Kyosho

#357

Quad Rider: This kit includes MIP high grade clutch shoes and our specially designed extension spring for a smooth and consistent power transfer.



A. Install MIP clutch shoes onto the flywheel pins using the *first* set of holes. This set-up allows the clutch to engage at low RPM's for smooth acceleration.


B. Install MIP clutch shoes onto the flywheel pins using the *second* set of holes. This set-up allows the clutch to engage at higher RPM's for more bottom end.

C. Install MIP clutch shoes onto the flywheel pins using the *third* set of holes. This set-up allows the clutch to engage at higher RPM's for even more bottom end. Good for high bite tracks.

CLUTCH SHOE SET UP:

INSTALLATION:

1. Remove the clutch bell from your motor and take the stock clutch shoes off of the flywheel.
2. Install MIP clutch shoes onto your flywheel using one of the three set-ups described on the left.
3. Secure the open hook ends of the clutch spring together to form a loop.
4. Use needle nose pliers to securely close the open hook ends of the clutch spring.
5. Slide the spring into the bottom half of the clutch shoe assembly. Use both of your thumbs to roll the spring over the top half, so the spring is completely around both clutch shoes.
6. Finish assembly using the stock clutch bell and re-install your motor into the car.



After rolling the spring over the clutch shoe assembly, make sure it sits flush inside the groove of the clutch shoes.

Moore's Ideal Products • 830 W. Golden Grove Way • Covina, CA 91722 • USA • 626-339-9008

www.miponline.com

RETURN TO LIST OF INSTRUCTION SHEETS