

Your new Failsafe unit is universally designed to work with all the popular brands of radio systems. It is equipped with universal male and female plugs. Be absolutely sure your radio system uses center red positive receiver/servo connections.

Installation

1. Remove your throttle servo plug from your receiver.
2. Plug your throttle servo into the female Failsafe plug.
3. Insert the male plug of your Failsafe in the throttle receiver slot.
4. Securely mount the Failsafe unit in your R/C vehicle or boat using double-sided tape. (You may want to mount your Failsafe after set-up.)

Set-up

1. Turn on your transmitter and power to your receiver.
2. From your transmitter throttle, set the amount of brake you would like applied to the throttle/brake servo when Failsafe is activated from loss of signal or battery power.
3. While holding this throttle position from your transmitter, push and hold the "set" button on the Failsafe for 2 seconds until the red LED is illuminated. The Failsafe position is the same for both battery and signal Failsafe.

Function

1. With loss of signal, the red LED will illuminate. When signal is regained, Failsafe and radio operation returns to normal.
2. With loss of battery power below 3.8V, the green LED will flash and the red LED will illuminate. With loss of battery power to your receiver, you must cycle power to your receiver in order to regain control.

LIMITED WARRANTY - U.S.A. and Canada only

DuraTrax warrants this product to be free from defects in material and workmanship for a period of 120 days from the date of purchase. During that time, we will repair or replace, at our option, any product that does not meet these standards. You will be required to provide proof of purchase date (receipt with UPC proof-of-purchase or invoice). If, during the 120 day warranty period, your DuraTrax product shows defects caused by abuse, misuse, or accident, it will be repaired or replaced, at our option, at a service charge not greater than 50% of the current retail list price. Be sure to include your daytime telephone number in case we need to contact you about your repair. Under no circumstances will the purchaser be entitled to consequential or incidental damages. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state. If you attempt to disassemble or repair this unit yourself, it may void the warranty. For service on your DuraTrax product, either in or out of warranty, send it post paid and insured to:

Hobby Services

3002 N. Apollo Drive, Suite 1

Champaign, IL 61822 U.S.A.

(217) 398-0007

www.hobbyservices.com

This warranty applies to USA and Canada only. For service in other countries, please inquire at the place of purchase. Customers residing outside the USA or Canada who wish to have service performed at our USA service center will be responsible for all postage charges.