

FRONT SUSPENSION	(CIRCLE OR CHECK CORRECT SETTIN	
DTOE IN / DTOE OUT.	0	3 🕽
TOE-IN / TOE-OUT:		20 10
FRONT RIDE HEIGHT:		
FRONT CAMBER: +°		
NOTES:		
		2
FRONT SHOCKS		INSIDE
OIL:		LE S
PISTON: DRILLED /	STANDARD	5
SPRING:, outside, outside-		
,337.652		
REAR SUSPENSION		
PIVOT SUPPORT: □ #2, □ #4		12
REAR PIVOT: NARROW, WIDE		
REAR RIDE HEIGHT: ° REAR CAMBER: + °		
NOTES:	HOLE IN HUB	HOLE IN
	HOLE IN HOB	TOWER
REAR SHOCKS	C _B A OUTS	IIDDLE
OIL:		☐ INSIDE (2.1 ○ ○ 5.4.3)
PISTON: DRILLED /	STANDARD	
SPRING:		
LIMITERS: INSIDE, OUTSIDE,		
TRANSMISSION & CHAS	SIS	
FRONT TIRE:	COMPOUND:	ENGINE:

TRANSMISSION & STIASSIS			
FRONT TIRE:	COMPOUND:	ENGINE:	
REAR TIRE:	COMPOUND:	CLUTCH BELL:SPUR GEAR:	
CLUTCH NOTES:		FUEL:	