



FRONT SUSPENSION	(CIRCLE OR CHECK CORRECT SETTINGS)
□TOE-IN / □TOE-OUT:°	Outside 4 1 3 1 3 1 1 3 1 1 1 1 1 1 1 1 1 1 1 1
FRONT CAMBER:°	
FRONT RIDE HEIGHT:	
SWAY BAR: No, YES - SIZE:	# OF WASHERS
NOTES:	
FRONT SHOCKS	
OIL:	DINSIDE DMIDDLE
PISTON: DRILLED / DSTANDARD SPRING:	DOUTSIDE
LIMITERS: INSIDE,OUTSIDE	
REAR SUSPENSION	
PIVOT SUPPORT: 0°, 2°	
REAR RIDE HEIGHT:	
REAR CAMBER:°  SWAY BAR: □ NO, □ YES - SIZE:	
NOTES:	HOLE IN
REAR SHOCKS	® Ø □ OUTSIDE
OIL: PISTON: □ DRILLED / □ STANDARD	INSIDE
SPRING:	
TRANSMISSION & CHASSIS  HYDRA-DRIVE:   NO,   YES-FLUID:   LIGHT,   STD.,   HEAVY	
FRONT TIRE: H.T., DG	MOTOR
REAR TIRE: H.T., DG	OLD, SILVER  PINION GEAR:
CHASSIS: ☐SHORT, ☐STANDARD, ☐LONG, ☐X	-LONG SPUR GEAR:
BATTERY DISCELL DISCELL BATTERY PLACE	CEMENT.